



AT TORBI 709M
AT TORBI 709MP preloaded
Technical Specifications



We make it visible.

AT TORBI 709M

AT TORBI 709MP preloaded



AT TORBI® 709M

Optic Design	Monofocal, bitoric, aspheric (aberration neutral)
Material	Hydrophilic acrylic (25 %) with hydrophobic surface
Optic Diameter	6.0 mm
Total Diameter	11.0 mm
Haptic Angulation	0°
Lens Design	Single-Piece, bitoric, MICS
Incision Size	1.5 mm
Company Labeled A-Constant ¹	118.3
Diopter Range	From -10.0 to +32.0 D Sphere: -10.0 to +32.0 D, 0.5 D increments Cylinder: +1.0 to +12.0 D, 0.5 D increments
ACD	5.14
Implantation in:	Bag
Injector / Cartridge Set ²	For IOLs from -10.0 to +24.0 sphere with +1.0 to +4.0 cylinder*: AT.Shooter A2-2000 / ACM2 (1.5 mm) <i>or</i> VISCOJECT™ 1.8 Injector Set <i>or</i> Single-use injector A6 / *AT.Smart Cartridge Set (1.8 mm) * For diopter range outside -10.0 to +24.0 D sphere with +1.0 to +4.0 D cylinder, the correct injector/cartridge set will be provided with the IOL

AT TORBI® 709MP preloaded

Optic Design	Monofocal, bitoric, aspheric (aberration neutral)
Material	Hydrophilic acrylic (25 %) with hydrophobic surface
Optic Diameter	6.0 mm
Total Diameter	11.0 mm
Haptic Angulation	0°
Lens Design	Single-Piece, bitoric, MICS
Incision Size	1.8 mm
Company Labeled A-Constant ¹	118.3
Diopter Range	From +6.0 to +24.0 D Sphere: +6.0 to +24.0 D, 0.5 D increments Cylinder: +1.0 to +4.0 D, 0.5 D increments
ACD	5.14
Implantation in:	Bag
Injector / Cartridge Set ²	BLUEMIXS® 180

¹ Please refer to our web pages for optimized A-Constants.

² Please refer to our web pages for the most up-to-date references.

